

# ECONOMY Breakers

Ergonomic design, high power performance



Fig. H 32

Fig. AH 28

- Ergonomic design for comfort and ease of use
- Compact, handy construction



## Technical specifications

Model	Blow frequency per min	Air demand *) m <sup>3</sup> /min	Chuck – Shank		Weight kg	Impact energy Joules	Weighted sum acceleration value **) m/s <sup>2</sup>
<b>With hand grip</b>							
CHH 10	3600	0.4	15.0 x 12.8 x 53.0	a)	2.6	7	12.0
H 32	2800	0.5	17.5 x 14.8 x 60.0	a)	4.5	12	10.0
CH 3	2400	0.7	17.5 x 14.8 x 60.0	a)	5.8	12	10.6
CHH 41	1800	1.0	17.5 x 14.8 x 60.0	b)	8.1	32	11.6
H 10	1300	0.9	S 22 x 82.5	c)	9.5	7	7.9
<b>With T-grip</b>							
AH 152	1600	1.1	S 25 x 108	c)	18.0	11	17.0
AH 201	1030	1.3	S 25 x 108	c)	20.0	13	13.9
AH 28	1100	1.7	S 32 x 152	c)	28.0	17	13.6

\*) At 6 bar \*\*) as per ISO8662 a) = Retaining spring b) = Retaining cap c) = Retaining catch  
Appropriate **chisels** are separately available: Pointed chisel, flat chisel, scaling chisel, spader



**KAESER KOMPRESSOREN AG**

P.O. Box 2143 – 96410 Coburg – GERMANY – Tel +49 9561 640-0 – Fax +49 9561 640130

e-mail: productinfo@kaeser.com – www.kaeser.com